

TRANSNET S+ - TN0506W

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : TRANSNET S+
Product code : TN0506W.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Liquid alkali
Cleaner for bodyworks
Professional use

1.3. Details of the supplier of the safety data sheet

Registered company name : ORAPI.
Address : PARC INDUSTRIEL DE LA PLAINE DE L'AIN - 225 ALLEE DES CEDRES.01150.SAINT-VULBAS.FRANCE.
Telephone : 33-(0)4-74-40-20-20. Fax : 33-(0)4-74-40-20-21.
fds@orapi.com

1.4. Emergency telephone number : 33-(0)1-45-42-59-59.

Association/Organisation : INRS .

Other emergency numbers

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Substance that is corrosive to metals, Category 1 (Met. Corr. 1, H290).
Skin irritation, Category 2 (Skin Irrit. 2, H315).
Serious eye damage, Category 1 (Eye Dam. 1, H318).
May produce an allergic reaction (EUH208).
This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Detergent mixture (see section 15).

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05

Signal Word :

DANGER

Product identifiers :

EC 200-573-9	TETRASODIUM ETHYLENE DIAMINE TETRAACETATE
EC 500-234-8	ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS
CAS 68439-46-3	ALCOHOLS C9-11 ETHOXYLATED
EC 215-185-5	SODIUM HYDROXIDE

Additional labeling :

EUH208 Contains QUATERNARY COMPOUND. May produce an allergic reaction.

Hazard statements :

H290	May be corrosive to metals.
H315	Causes skin irritation.
H318	Causes serious eye damage.

TRANSNET S+ - TN0506W

Precautionary statements - Prevention :

P234 Keep only in original packaging.
P264 Wash hands thoroughly after handling.
P280 Wear protective gloves/eye protection/face protection.

Precautionary statements - Response :

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor/physician.
P390 Absorb spillage to prevent material damage.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 64-02-8 EC: 200-573-9 REACH: 01-2119486762-27 TETRASODIUM ETHYLENE DIAMINE TETRAACETATE	GHS07, GHS05, GHS08 Dgr Acute Tox. 4, H302 Eye Dam. 1, H318 Acute Tox. 4, H332 STOT RE 2, H373		2.5 $\leq$ x % < 10
CAS: 15763-76-5 EC: 239-854-6 REACH: 01-2119489411-37 P-CUMENESULFONATE DE SODIUM	GHS07 Wng Eye Irrit. 2, H319		2.5 $\leq$ x % < 10
CAS: 68891-38-3 EC: 500-234-8 REACH: 01-2119488639-16 ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS	GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412		2.5 $\leq$ x % < 10
CAS: 68439-46-3 REACH: 02-2119495489-16 ALCOHOLS C9-11 ETHOXYLATED	GHS07, GHS05 Dgr Acute Tox. 4, H302 Eye Dam. 1, H318		2.5 $\leq$ x % < 10
CAS: 1310-73-2 EC: 215-185-5 REACH: 01-2119457892-27 SODIUM HYDROXIDE	GHS05 Dgr Met. Corr. 1, H290 Skin Corr. 1A, H314	[1]	0 $\leq$ x % < 2.5
CAS: 784144-40-7 EC: 630-545-5 QUATERNARY COMPOUND	GHS05, GHS07 Dgr Skin Sens. 1, H317 Eye Dam. 1, H318		0 $\leq$ x % < 2.5

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of massive inhalation transport the patient to the free air and keep it with the heat and rest.

Do not absorb nothing by mouth.

TRANSNET S+ - TN0506W

Consult a physician in case of disorder.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

DO NOT induce vomiting. Keep at rest.

If swallowed accidentally, call a doctor to assess the need for monitoring and subsequent treatment in hospital. Show him the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- powder
- carbon dioxide (CO₂)

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Because of the toxicity of gases emitted during the thermal decomposition products, speakers will be equipped with respirators autonomous insulating.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

TRANSNET S+ - TN0506W

6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Ensure adequate ventilation, especially in confined areas.

Fire prevention :

Prevent access by unauthorised personnel.

Handle in well ventilated areas.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid eye contact with this mixture at all times.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

The floor must be impermeable and form a collecting basin so that in case of accidental spillage, the liquid can not spread beyond.

Keep container tightly closed and in a cool, dry and well-ventilated place.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
1310-73-2	-	2	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1310-73-2	- ppm - mg/m ³	- ppm 2 mg/m ³			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

SODIUM HYDROXIDE (CAS: 1310-73-2)

Final use:

Exposure method:

Potential health effects:

DNEL :

Workers.

Inhalation.

Long term local effects.

1 mg of substance/m³

Final use:

Exposure method:

Potential health effects:

Consumers.

Inhalation.

Long term local effects.

TRANSNET S+ - TN0506W

DNEL : 1 mg of substance/m3

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex
- PVC (polyvinyl chloride)
- Butyl Rubber (Isobutylene-isoprene copolymer)
- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Fluid liquid.

Color : blue

Odor : Lemon

Important health, safety and environmental information

pH : Not stated.

Strongly basic.

pH (aqueous solution) : 11.5 +/- 0.3 à 10g/l

Boiling point/boiling range : Not specified.

Flash point interval : Not relevant.

Vapour pressure (50°C) : Not relevant.

Density : 1.15 +/- 0.01 (20°C)

Water solubility : Soluble.

Melting point/melting range : Not specified.

TRANSNET S+ - TN0506W

Self-ignition temperature : Not specified.
Decomposition point/decomposition range : Not specified.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

Mixture which by chemical action can corrode and even destroy metals.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

Exposed to high temperatures, the mixture may release dangerous decomposition products, such as carbon monoxide and dioxide, smoke and nitrogen oxide.

10.4. Conditions to avoid

Avoid :

- frost
- heat

10.5. Incompatible materials

Keep away from :

- acids
- strong acids
- metals

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

11.1.1. Substances

Acute toxicity :

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE (CAS: 64-02-8)

Oral route : LD₅₀ = 1780 mg/kg

Inhalation route (Dusts/mist) : 1 < LC₅₀ ≤ 5 mg/l
Species : Rat
Duration of exposure : 4 h

11.1.2. Mixture

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

ALCOHOLS C9-11 ETHOXYLATED (CAS: 68439-46-3)

Fish toxicity : LC₅₀ = 12 mg/l
Duration of exposure : 96 h

Crustacean toxicity : EC₅₀ = 5.4 mg/l

TRANSNET S+ - TN0506W

	Duration of exposure : 48 h
	NOEC = 2.58 mg/l
	Duration of exposure : 21 days
Algae toxicity :	ECr50 > 8.9 mg/l
	Duration of exposure : 72 h
	NOEC = 8.9 mg/l
	Duration of exposure : 72 h
ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)	
Fish toxicity :	LC50 = 7.1 mg/l
	Species : Danio rerio
	Duration of exposure : 96 h
	OECD Guideline 203 (Fish, Acute Toxicity Test)
Crustacean toxicity :	EC50 = 7.4 mg/l
	Duration of exposure : 48 h
	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Algae toxicity :	ECr50 = 27.7 mg/l
	Duration of exposure : 72 h
	OECD Guideline 201 (Alga, Growth Inhibition Test)
	NOEC = 0.95 mg/l
	Duration of exposure : 72 h
TETRASODIUM ETHYLENE DIAMINE TETRAACETATE (CAS: 64-02-8)	
Fish toxicity :	LC50 > 100 mg/l
	Duration of exposure : 96 h
Crustacean toxicity :	EC50 > 500 mg/l
	Species : Daphnia magna
	Duration of exposure : 24 h
Algae toxicity :	ECr50 > 100 mg/l
	Duration of exposure : 72 h
SODIUM HYDROXIDE (CAS: 1310-73-2)	
Fish toxicity :	LC50 = 125 mg/l
	Species : Gambusia affinis
	Duration of exposure : 96 h
Crustacean toxicity :	EC50 = 76 mg/l
	Species : Daphnia magna
	Duration of exposure : 48 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

SODIUM HYDROXIDE (CAS: 1310-73-2)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

ALCOHOLS C9-11 ETHOXYLATED (CAS: 68439-46-3)

Biodegradability : Rapidly degradable.

TRANSNET S+ - TN0506W

ALCOHOLS, C12-14, ETHOXYLATED, SULFATES, SODIUM SALTS (CAS: 68891-38-3)
Biodegradability : Rapidly degradable.

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE (CAS: 64-02-8)
Biodegradability : Non-rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

ALCOHOLS C9-11 ETHOXYLATED (CAS: 68439-46-3)
Bioaccumulation : BCF < 800

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2016).

14.1. UN number

3267

14.2. UN proper shipping name

UN3267=CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.

(sodium hydroxide, tetrasodium ethylene diamine tetraacetate)

14.3. Transport hazard class(es)

- Classification :



8

14.4. Packing group

III

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C7	III	8	80	5 L	274	E1	3	E

TRANSNET S+ - TN0506W

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	8	-	III	5 L	F-A,S-B	223 274	E1

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	8	-	III	852	5 L	856	60 L	A3 A803	E1
	8	-	III	Y841	1 L	-	-	A3 A803	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2016/1179. (ATP 9)

- Container information:

No data available.

- Particular provisions :

No data available.

- Labelling for detergents (EC Regulation No. 648/2004,907/2006) :

- less than 5 % : anionic surfactants
- less than 5 % : cationic surfactants
- less than 5 % : nonionic surfactants
- 5 % or over but less than 15 % : EDTA and salts thereof
- perfumes
- allergenic fragrances :
d-limonene

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

The use of the preparation is restricted to professional users.

Modifications brought with regard to the previous version :

- classification Section 2

Wording of the phrases mentioned in section 3 :

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H302 + H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure .
H412	Harmful to aquatic life with long lasting effects.

TRANSNET S+ - TN0506W

Abbreviations :

DNEL : Derived No-Effect Level
ADR : European agreement concerning the international carriage of dangerous goods by Road.
IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.
WGK : Wassergefährdungsklasse (Water Hazard Class).
GHS05 : Corrosion
PBT: Persistent, bioaccumulable and toxic.
vPvB : Very persistent, very bioaccumulable.
SVHC : Substances of very high concern.