

TRANSNET SGC - TN054000

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : TRANSNET SGC
Product code : TN054000.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Bodywork shampoo
Vehicles cleaners.
Professional use

1.3. Details of the supplier of the safety data sheet

Registered company name : TRANSNET .
Address : Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres.01150.Saint-Vulbas.France.
Telephone : 33-(0)4-74-40-21-00. Fax : 33-(0)4-74-40-21-01.
fds@orapi.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

Other emergency numbers

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin corrosion, Category 1 (Skin Corr. 1, H314).
Serious eye damage, Category 1 (Eye Dam. 1, H318).
Skin sensitisation, Category 1 (Skin Sens. 1, H317).
This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.
This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Detergent mixture (see section 15).

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05



GHS07

Signal Word :

DANGER

Product identifiers :

CAS 68439-46-3 ALCOHOLS C9-11 ETHOXYLATED
EC 630-545-5 1-PROPANEAMMINIUM, 3-AMINO-N,N,N-TRIMETHYL-, N-(ETHOXYLATED CASTOR OIL ACYL)
DERIVS., ME SULFATE (6-EO + 10.7-EO)
EC 215-185-5 SODIUM HYDROXIDE

Hazard statements :

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

Precautionary statements - Prevention :

P280 Wear protective gloves, protective clothing, eye protection, face protection.

Precautionary statements - Response :

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

TRANSNET SGC - TN054000

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 0586 CAS: 68439-46-3 ALCOHOLS C9-11 ETHOXYLATED	GHS07, GHS05 Dgr Acute Tox. 4, H302 Eye Dam. 1, H318		$2.5 \leq x \% < 10$
INDEX: 0411 CAS: 784144-40-7 EC: 630-545-5 1-PROPANEAMMINIUM, 3-AMINO-N,N,N-TRIMETHYL-, N-(ETHOXYLATED CASTOR OIL ACYL) DERIVS., ME SULFATE (6-EO + 10.7-EO)	GHS05, GHS07 Dgr Skin Sens. 1, H317 Eye Dam. 1, H318		$0 \leq x \% < 2.5$
INDEX: 61791_148 CAS: 61791-14-8 EC: 500-152-2 ETHOXYLATED FATTY AMINE	GHS07, GHS05 Dgr Acute Tox. 4, H302 Eye Dam. 1, H318 Aquatic Chronic 3, H412		$0 \leq x \% < 2.5$
INDEX: 15763_76_5 CAS: 15763-76-5 EC: 239-854-6 REACH: 01-2119489411-37 P-CUMENESULFONATE DE SODIUM	GHS07 Wng Eye Irrit. 2, H319		$0 \leq x \% < 2.5$
INDEX: 1310_73_2 CAS: 1310-73-2 EC: 215-185-5 REACH: 01-2119457892-27 SODIUM HYDROXIDE	GHS05 Dgr Met. Corr. 1, H290 Skin Corr. 1A, H314 Eye Dam. 1, H318	[1]	$0 \leq x \% < 1$

(Full text of H-phrases: see section 16)

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.
NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of massive inhalation transport the patient to the free air and keep it with the heat and rest.
Do not absorb nothing by mouth.
Consult a physician in case of disorder.

TRANSNET SGC - TN054000

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Remove any soiled or splashed clothing immediately.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

If swallowed accidentally, call a doctor to assess the need for monitoring and subsequent treatment in hospital. Show him the label.

Keep warm. Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- powder
- carbon dioxide (CO₂)

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Because of the toxicity of gases emitted during the thermal decomposition products, speakers will be equipped with respirators autonomous insulating.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

If the spill is large, evacuate all personnel and only allow intervention by trained operators equipped with safety equipment.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

TRANSNET SGC - TN054000

6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

Individuals with a history of skin sensitisation should not, under any circumstance, handle this mixture.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Do not mix with acid.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

The floor must be impermeable and form a collecting basin so that in case of accidental spillage, the liquid can not spread beyond.

Keep container tightly closed and in a cool, dry and well-ventilated place.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1310-73-2			2 mg/m3		

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
1310-73-2	-	2	-	-	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2011) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1310-73-2	- ppm - mg/m ³	- ppm 2 mg/m ³			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

SODIUM HYDROXIDE (CAS: 1310-73-2)

Final use:

Exposure method:

Potential health effects:

DNEL :

Exposure method:

Potential health effects:

Workers.

Dermal contact.

Short term local effects.

2 mg/kg body weight/day

Inhalation.

Long term local effects.

TRANSNET SGC - TN054000

DNEL : 1 mg of substance/m3

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 1 mg of substance/m3

Final use: **Consumers.**
Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 1 mg of substance/m3

P-CUMENESULFONATE DE SODIUM (CAS: 15763-76-5)

Final use: **Workers.**
Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 136.25 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Long term local effects.
DNEL : 0.096 mg of substance/cm2

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 26.9 mg of substance/m3

Final use: **Consumers.**
Exposure method: Ingestion.
Potential health effects: Long term systemic effects.
DNEL : 3.8 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Long term systemic effects.
DNEL : 68.1 mg/kg body weight/day

Exposure method: Dermal contact.
Potential health effects: Long term local effects.
DNEL : 0.048 mg of substance/cm2

Exposure method: Inhalation.
Potential health effects: Long term systemic effects.
DNEL : 6.6 mg of substance/m3

Predicted no effect concentration (PNEC):

P-CUMENESULFONATE DE SODIUM (CAS: 15763-76-5)

Environmental compartment: Soil.
PNEC : 0.037 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.23 mg/l

Environmental compartment: Sea water.
PNEC : 0.023 mg/l

Environmental compartment: Intermittent waste water.
PNEC : 2.3 mg/l

Environmental compartment: Fresh water sediment.
PNEC : 0.862 mg/kg

TRANSNET SGC - TN054000

Environmental compartment: Marine sediment.
PNEC : 0.0862 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 100 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

- PVC (polyvinyl chloride)

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))

- Butyl Rubber (Isobutylene-isoprene copolymer)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Wear suitable protective clothing, in particular overalls and boots. These items must be kept in good condition and cleaned after use.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Fluid liquid.

Color : orange

Important health, safety and environmental information

pH : Not stated.

Strongly basic.

pH (aqueous solution) : 11.1 (10g/L)

Boiling point/boiling range : Not specified.

Flash point interval : Not relevant.

TRANSNET SGC - TN054000

Vapour pressure (50°C) :	Not relevant.
Density :	1.060 +/- 0.005
Water solubility :	Soluble.
Melting point/melting range :	Not specified.
Self-ignition temperature :	Not specified.
Decomposition point/decomposition range :	Not specified.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

Exothermic reaction with acids.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

Exposed to high temperatures, the mixture may release dangerous decomposition products, such as carbon monoxide and dioxide, smoke and nitrogen oxide.

10.4. Conditions to avoid

Avoid :

- frost
- heat

10.5. Incompatible materials

Keep away from :

- acids
- strong acids

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely, visible necrosis through the epidermis and into the dermis, following exposure for up to three minutes.

Corrosive reactions are typified by ulcers, bleeding, bloody scabs, and, by the end of observation at 14 days, by discolouration due to blanching of the skin, complete areas of alopecia, and scars.

May cause an allergic reaction by skin contact.

11.1.1. Substances

Acute toxicity :

ALCOHOLS C9-11 ETHOXYLATED (CAS: 68439-46-3)

Oral route : 300 < LD50 <= 2000 mg/kg
Species : Rat

11.1.2. Mixture

Skin corrosion/skin irritation :

Corrosive classification is based on an extreme pH value.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

ALCOHOLS C9-11 ETHOXYLATED (CAS: 68439-46-3)

Fish toxicity : LC50 = 12 mg/l
Duration of exposure : 96 h

Crustacean toxicity : EC50 = 5.4 mg/l

TRANSNET SGC - TN054000

Duration of exposure : 48 h

NOEC = 2.58 mg/l
Duration of exposure : 21 days

Algae toxicity :

ECr50 > 8.9 mg/l
Duration of exposure : 72 h

NOEC = 8.9 mg/l
Duration of exposure : 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

ALCOHOLS C9-11 ETHOXYLATED (CAS: 68439-46-3)

Biodegradability : Rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

ALCOHOLS C9-11 ETHOXYLATED (CAS: 68439-46-3)

Bioaccumulation : BCF < 800

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2019 - IMDG 2018 - ICAO/IATA 2019).

14.1. UN number

3267

14.2. UN proper shipping name

UN3267=CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S.
(sodium hydroxide)

TRANSNET SGC - TN054000

14.3. Transport hazard class(es)

- Classification :



8

14.4. Packing group

III

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	8	C7	III	8	80	5 L	274	E1	3	E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	8	-	III	5 L	F-A, S-B	223 274	E1	Category A SW2	SGG18 SG35

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	8	8	III	852	5 L	856	60 L	A3 A803	E1
	8	8	III	Y841	1 L	-	-	A3 A803	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available.

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2018/1480 (ATP 13)
- EU Regulation No. 1272/2008 amended by EU Regulation No. 2019/521 (ATP 12)

- Container information:

No data available.

- Particular provisions :

No data available.

- Labelling for detergents (EC Regulation No. 648/2004,907/2006) :

- less than 5 % : cationic surfactants
- less than 5 % : nonionic surfactants

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Modifications brought with regard to the previous version :

- section 2
- section 3.

TRANSNET SGC - TN054000

Wording of the phrases mentioned in section 3 :

H290	May be corrosive to metals.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level
PNEC : Predicted No-Effect Concentration
ADR : European agreement concerning the international carriage of dangerous goods by Road.
IMDG : International Maritime Dangerous Goods.
IATA : International Air Transport Association.
ICAO : International Civil Aviation Organisation
RID : Regulations concerning the International carriage of Dangerous goods by rail.
GHS05 : Corrosion
GHS07 : Exclamation mark
PBT: Persistent, bioaccumulable and toxic.
vPvB : Very persistent, very bioaccumulable.
SVHC : Substances of very high concern.