

TRANSNET SUPERCREAM BOX - TN051Z0

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : TRANSNET SUPERCREAM BOX
Product code : TN051Z0.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Bodywork shampoo
For washing station.

1.3. Details of the supplier of the safety data sheet

Registered company name : TRANSNET .
Address : Parc Industriel de la Plaine de l'Ain - 225 allée des Cèdres.01150.Saint-Vulbas.France.
Telephone : 33-(0)4-74-40-21-00. Fax : 33-(0)4-74-40-21-01.
fds@orapi.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

Other emergency numbers

Emergency Action: In the event of a medical enquiry involving this product, please contact your doctor or local hospital accident and emergency department.

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Skin irritation, Category 2 (Skin Irrit. 2, H315).
Serious eye damage, Category 1 (Eye Dam. 1, H318).
May produce an allergic reaction (EUH208).
This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.
This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

2.2. Label elements

Detergent mixture (see section 15).

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS05

Signal Word :

DANGER

Product identifiers :

EC 200-573-9	TETRASODIUM ETHYLENE DIAMINE TETRAACETATE
EC 500-234-8	ALKYL ETHER SULFATE C12-14, ETHOXYLATED, SODIUM SALT
EC 307-055-2	SULFONIC ACIDS, C14-17-SEC-ALKANE, SODIUM SALTS
EC 215-181-3	POTASSIUM HYDROXIDE

Additional labeling :

EUH208 Contains QUATERNARY COMPOUND. May produce an allergic reaction.

Hazard statements :

H315	Causes skin irritation.
H318	Causes serious eye damage.

Precautionary statements - Prevention :

P264	Wash hands thoroughly after handling.
P280	Wear protective gloves/eye protection/face protection.

TRANSNET SUPERCREAM BOX - TN051Z0

Precautionary statements - Response :

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER or doctor/physician.
P332 + P313 If skin irritation occurs: Get medical advice/attention.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition :

Identification	(EC) 1272/2008	Note	%
INDEX: 0706 CAS: 64-02-8 EC: 200-573-9 REACH: 01-2119486762-27 TETRASODIUM ETHYLENE DIAMINE TETRAACETATE	GHS07, GHS05, GHS08 Dgr Acute Tox. 4, H302 Eye Dam. 1, H318 Acute Tox. 4, H332 STOT RE 2, H373		0 $\leq$ x % < 2.5
INDEX: 68891_38_3. CAS: 68891-38-3 EC: 500-234-8 REACH: 01-2119488639-16 ALKYL ETHER SULFATE C12-14, ETHOXYLATED, SODIUM SALT	GHS05 Dgr Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 3, H412		0 $\leq$ x % < 2.5
INDEX: 1173 CAS: 97489-15-1 EC: 307-055-2 REACH: 01-2119489924-20 SULFONIC ACIDS, C14-17-SEC-ALKANE, SODIUM SALTS	GHS07, GHS05 Dgr Acute Tox. 4, H302 Skin Irrit. 2, H315 Eye Dam. 1, H318		0 $\leq$ x % < 2.5
INDEX: 019_002_00_8 CAS: 1310-58-3 EC: 215-181-3 REACH: 01-2119487136-33 POTASSIUM HYDROXIDE	GHS06, GHS05 Dgr Met. Corr. 1, H290 Acute Tox. 3, H301 Skin Corr. 1A, H314	[1]	0 $\leq$ x % < 2.5
INDEX: 0411 CAS: 784144-40-7 EC: 630-545-5 QUATERNARY COMPOUND	GHS05, GHS07 Dgr Skin Sens. 1, H317 Eye Dam. 1, H318		0 $\leq$ x % < 2.5

Information on ingredients :

[1] Substance for which maximum workplace exposure limits are available.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation :

In the event of an allergic reaction, seek medical attention.

In the event of massive inhalation transport the patient to the free air and keep it with the heat and rest.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

Regardless of the initial state, refer the patient to an ophthalmologist and show him the label.

TRANSNET SUPERCREAM BOX - TN051Z0

In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

In the event of swallowing :

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention immediately, showing the label.

DO NOT induce vomiting. Keep at rest.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- foam
- powder
- carbon dioxide (CO₂)

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Neutralise with an acidic decontaminant.

If the ground is contaminated, once the product has been recovered by sponging with an inert and non-combustible absorbent material, wash the contaminated area in plenty of water.

Clean preferably with a detergent, do not use solvents.

TRANSNET SUPERCREAM BOX - TN051Z0

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Emergency showers and eye wash stations will be required in facilities where the mixture is handled constantly.

Do not mix with acid.

Fire prevention :

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Avoid eye contact with this mixture at all times.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep the container tightly closed.

Store in original packaging.

Stay away from products sensitive to alkaline.

Packaging

Always keep in packaging made of an identical material to the original.

Suitable packaging materials :

- Polyethylene

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits :

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1310-58-3			2 mg/m3		

- France (INRS - ED984 :2016) :

CAS	VME-ppm :	VME-mg/m3 :	VLE-ppm :	VLE-mg/m3 :	Notes :	TMP No :
1310-58-3	-	-	-	2	-	-

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
1310-58-3		2 mg/m3			

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

ALKYL ETHER SULFATE C12-14, ETHOXYLATED, SODIUM SALT (CAS: 68891-38-3)

Final use:

Exposure method:

Potential health effects:

DNEL :

Exposure method:

Potential health effects:

DNEL :

Workers.

Dermal contact.

Long term systemic effects.

2750 mg/kg body weight/day

Inhalation.

Long term systemic effects.

175 mg of substance/m3

TRANSNET SUPERCREAM BOX - TN051Z0

Final use:

Exposure method:
Potential health effects:
DNEL :

Consumers.

Ingestion.
Long term systemic effects.
15 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Dermal contact.
Long term systemic effects.
1650 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
52 mg of substance/m3

Predicted no effect concentration (PNEC):

ALKYL ETHER SULFATE C12-14, ETHOXYLATED, SODIUM SALT (CAS: 68891-38-3)

Environmental compartment: Soil.
PNEC : 0.946 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.24 mg/l

Environmental compartment: Sea water.
PNEC : 0.024 mg/l

Environmental compartment: Intermittent waste water.
PNEC : 0.071 mg/l

Environmental compartment: Fresh water sediment.
PNEC : 5.45 mg/kg

Environmental compartment: Marine sediment.
PNEC : 0.545 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 1000 mg/l

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Wear suitable protective gloves in the event of prolonged or repeated skin contact.

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Natural latex

TRANSNET SUPERCREAM BOX - TN051Z0

- PVC (polyvinyl chloride)

Recommended properties :

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing :

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information :

Physical state : Fluid liquid.

Colour: Colourless

Important health, safety and environmental information

pH : 12.60 .
Strongly basic.

pH (aqueous solution) : 11.5 (à 1%)

Boiling point/boiling range : Not specified.

Flash point interval : Not relevant.

Vapour pressure (50°C) : Not relevant.

Density : 1.03

Water solubility : Soluble.

Melting point/melting range : Not specified.

Self-ignition temperature : Not specified.

Decomposition point/decomposition range : Not specified.

9.2. Other information

No data available.

SECTION 10 : STABILITY AND REACTIVITY

10.1. Reactivity

Exothermic reaction with acids.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Avoid :

- heat

- frost

10.5. Incompatible materials

Keep away from :

- acids

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO2)

TRANSNET SUPERCREAM BOX - TN051Z0

SECTION 11 : TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

May cause irreversible damage to the skin; namely inflammation of the skin or the formation of erythema and eschar or oedema following exposure up to four hours.

May have irreversible effects on the eyes, such as tissue damage in the eye, or serious physical decay of sight, which is not fully reversible by the end of observation at 21 days.

Serious eye damage is typified by the destruction of cornea, persistent corneal opacity and iritis.

11.1.1. Substances

Acute toxicity :

ALKYL ETHER SULFATE C12-14, ETHOXYLATED, SODIUM SALT (CAS: 68891-38-3)

Dermal route : LD50 > 200 mg/kg
Species : Rat
OECD Guideline 402 (Acute Dermal Toxicity)

POTASSIUM HYDROXIDE (CAS: 1310-58-3)

Oral route : LD50 = 273 mg/kg
Species : Rat

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE (CAS: 64-02-8)

Oral route : LD50 = 1780 mg/kg

Inhalation route (Dusts/mist) : 1 < LC50 <= 5 mg/l
Species : Rat

Skin corrosion/skin irritation :

ALKYL ETHER SULFATE C12-14, ETHOXYLATED, SODIUM SALT (CAS: 68891-38-3)

Species : Rabbit

Effect observed : Overall irritation score

Species : Rabbit

Respiratory or skin sensitisation :

ALKYL ETHER SULFATE C12-14, ETHOXYLATED, SODIUM SALT (CAS: 68891-38-3)

Guinea Pig Maximisation Test (GMPT) : Non-sensitiser.
Species : Others
OECD Guideline 406 (Skin Sensitisation)

11.1.2. Mixture

Skin corrosion/skin irritation :

The irritant classification is based on the high/low pH value without irritation tests having been performed.

Serious damage to eyes/eye irritation :

Corrosive classification is based on an extreme pH value.

Respiratory or skin sensitisation :

Contains at least one sensitising substance. May cause an allergic reaction.

SECTION 12 : ECOLOGICAL INFORMATION

12.1. Toxicity

12.1.1. Substances

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE (CAS: 64-02-8)

Fish toxicity : LC50 > 100 mg/l
Duration of exposure : 96 h

Crustacean toxicity : EC50 > 500 mg/l
Species : Daphnia magna
Duration of exposure : 24 h

TRANSNET SUPERCREAM BOX - TN051Z0

Algae toxicity : ECr50 > 100 mg/l
Duration of exposure : 72 h

ALKYL ETHER SULFATE C12-14, ETHOXYLATED, SODIUM SALT (CAS: 68891-38-3)
Fish toxicity : LC50 = 7.1 mg/l
Species : Danio rerio
Duration of exposure : 96 h
OECD Guideline 203 (Fish, Acute Toxicity Test)

Crustacean toxicity : EC50 = 7.4 mg/l
Species : Daphnia magna
Duration of exposure : 48 h
OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

0,1 < NOEC <= 1 mg/l
Species : Daphnia magna

Algae toxicity : ECr50 = 27.7 mg/l
Species : Desmodesmus subspicatus
Duration of exposure : 72 h
OECD Guideline 201 (Alga, Growth Inhibition Test)

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

ALKYL ETHER SULFATE C12-14, ETHOXYLATED, SODIUM SALT (CAS: 68891-38-3)
Biodegradability : Rapidly degradable.

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE (CAS: 64-02-8)
Biodegradability : Non-rapidly degradable.

12.3. Bioaccumulative potential

12.3.1. Substances

ALKYL ETHER SULFATE C12-14, ETHOXYLATED, SODIUM SALT (CAS: 68891-38-3)
Octanol/water partition coefficient : log K_{ow} < 1

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

TRANSNET SUPERCREAM BOX - TN051Z0

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

SECTION 15 : REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

- Classification and labelling information included in section 2:

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.

- Container information:

No data available.

- Particular provisions :

No data available.

- Labelling for detergents (EC Regulation No. 648/2004,907/2006) :

- less than 5 % : anionic surfactants
- less than 5 % : cationic surfactants
- less than 5 % : nonionic surfactants
- less than 5 % : EDTA and salts thereof
- perfumes

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

The use of the preparation is restricted to professional users.

Modifications brought with regard to the previous version :

Update according to Directive EU n° 2015/830.

Wording of the phrases mentioned in section 3 :

H290	May be corrosive to metals.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H302 + H332	Harmful if swallowed or if inhaled.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure .
H412	Harmful to aquatic life with long lasting effects.

Abbreviations :

DNEL : Derived No-Effect Level

PNEC : Predicted No-Effect Concentration

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

TRANSNET SUPERCREAM BOX - TN051Z0

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS05 : Corrosion